

ENDURO TRAIL-ADV

2023

70

ON

OFF

30



- Classified for 70% on-road use and designed for all-round performance and confidence on paved roads as well as off-road.
- Multi compound tread technology with a longitudinal pattern ensures ultimate grip and durability in ON/OFF.
- Recommended for Dual-Purpose Adventure Touring motorcycles.

Inch	Code	Tyre size	LI/SS	Type (TL/TT)	Homologation	Measuring rim width	Permitted rim width range	Tyre dimensions E.T.R.T.O. (mm)				Tube option 1	Tube option 2
								Design		Max. in service			
								Section width	Overall diameter	Overall width	Overall diameter		
FRONT													
19	70001201	110/80R19	59V	TL	E D	2.50	2.50-3.00	109	659	117	671		
19	70001096	120/70R19	60W	TL/TT	E D	3.50	3.00-3.75	122	651	131	663		
21	70001202	90/90R21 (3.00R21)	54V	TL	E D	2.15	1.85-2.50	90	695	99	707	70000853	70000878
REAR													
17	70001199	150/70R17	69V	TL	E D	4.25	4.00-4.50	151	642	162	656		
17	70001095	170/60R17	72W	TL/TT	E D	4.50	4.50-5.50	168	636	180	650		
18	70001200	150/70R18	70V	TL	E D	4.25	4.00-4.50	151	667	162	681	70000855	

* Mitas ENDURO TRAIL-ADV is not distributed in the following countries: France, UK, Italy, Germany, USA and China.

MC-24

70

ON

OFF

30



- Classified for 70% on-road use and designed for all-round performance and confidence on paved roads as well as off-road.
- Heavy-Duty compound combined with a deep crossed pattern ensure traction and predictable performance in ON/OFF.
- Recommended for Dual-Purpose Adventure Touring motorcycles.

Inch	Code	Tyre size	LI/SS	Type (TL/TT)	Homologation	Measuring rim width	Permitted rim width range	Tyre dimensions E.T.R.T.O. (mm)				Tube option 1	Tube option 2
								Design		Max. in service			
								Section width	Overall diameter	Overall width	Overall diameter		
FRONT													
19	70000538	100/90-19	57S	TL*	E D I	2.50	2.15-2.75	101	663	111	675	70000870	
21	70000542	90/90-21	54S	TT	E D I	2.15	1.85-2.50	90	695	99	707	70000878	70000853
REAR													
17	70000540	120/90-17	64S	TL*	E D I	2.75	2.50-3.00	119	648	131	664	70000852	
17	70000541	130/80-17	65S	TL*	E D I	3.00	2.50-3.50	129	640	142	654	70000852	
18	70000539	120/80-18	62S	TT	E D	2.75	2.50-3.00	119	649	131	633	70000855	70000844

