

KENDA ATV-REIFEN

KENDA

Anwendungsempfehlung

geeignet für =

	Reifen- bezeichnung	Profil	Trocken, harter & felsiger Unter- grund	Trocken, lockerer & steiniger Untergrund	lehmig, lockerer Untegrund, Gras	Schlamm Sand	Schnee
ATV	Front Max	K284					
	Scorpion	K290					
	Dune Runner	K292					
	Dune Runner	K298					
	Bear Claw	K299					
	Bear Claw II	K587					
	Dominator	K300F					
		K300					
	Pathfinder	K530F					
		K530					
	Klaw	K532F					
		K532FA					
		K533					
	Sand Gecko	K534					
	Sand Gecko Plus	K534A					
	Knarly XC	K535A					
	Knarly ST	K535MX					
	Bounter Hunter ST	K537					
	Executioner	K538					
	-	K542F					
	-	K543					
	Speedracer	K546F					
		K547					
	-	K570					
	Road Go	K572					
	Bear Claw Ex	K573F					
		K573					
	-	K576					
	-	K578F					
	-	K579					
	Kutter MX	K580F					
		K581					
	Kutter XC	K580F					
		K581					
	-	K582F					
	-	K583					
	Snow Mad	K584					
	Bounter Hunter HT	K585					
	Parker D-T	K580F					
		K581					

Reifendimensionserläuterung

Erklärung der Dimensionsbezeichnungen	
165 / 70 - 10	20 x 10 - 8
↓	↓
↓	↓
↓	↓
Ø Felge in Zoll	Ø Felge in Zoll
Reifenhöhe in % zur Breite	Reifenbreite in Zoll
Reifenbreite in mm	Gesamt Ø Reifen in Zoll